

A-120-1

아연합금제



록 핸들

LOCK HANDLES

록 핸들

A

핸들 · 손잡이 · 노브 · 주변기기

크레몬

롤러 잠금

특강 밀폐
핸들

프리저 밀폐

평면 스윙

평면 핸들

팝 핸들

리프트 핸들

여저스터 핸들

래치식



A-120-1





A-120-1-H



[A-120-1]



[A-120-1-H]



패널 구멍 치수 Panel drilling dimensions



특징 Feature

- 핸들의 소형화로 휴대에 편리합니다.
- 360° 회전
- Handle is small-sized so easy to carry.
- Turning angle is 360°.

사양

- 재질: 본체/아연합금(ZDC)
핸들/냉간 압연 강판(SPCC)
- 표면 마무리: 본체/크롬 도금(MZCr)
핸들/아연 도금 크로메이트 처리(MFZn-C)

용도

- 소형 배분전반·제어반

비고



- 특별한 표면 처리는 상담해 주십시오.
- 스톱퍼 부착용 M8 너트의 조임 토크는 6.2N·m 이하로 해주십시오.
- 본 제품의 스톱퍼 부착용 나사는 풀림 방지를 위해 '풀림 방지제'를 도포할 것을 권장합니다.

Specifications

- Material: Main body: Zinc alloy (ZDC)
Handle: Cold rolled steel plate (SPCC)
- Finish: Main body: Chrome plating (MZCr)
Handle: Zinc Plating chromate treatment (MFZn-C)

Specific use Remarks



- Small power/distribution and control boards
- Set the torque of the M8 nut for stopper plate within 6.2 N·m.
- It is recommended that thread-locking fluid be used to prevent loosening of the mounting screws for the catch.

상품번호 Product No.	RoHS 10	최대 적용 판 두께 Max. applicable panel thickness	제품질량(g) Mass	코드 Code
A-120-1	●	3	40	00256
A-120-1-H	●		10	00257

●: RoHS10 대응품

▲: RoHS10에 대응가능합니다.