

특징 Feature

- 난연재(UL94 V-0 적합)를 사용. (C-30-CS-1~4·7~10-EP-UL)
- 패널 구멍에 원터치로 세팅
- 비이행성 고무(오염 시험 JIS K6267 이상 없음)
- Flame-retardant rubber (conforms to UL94 V-0) is used. (C-30-CS-1~4·7~10-EP-UL)
- Can be attached one-touch to the hole of a panel.
- Non-transmutation rubber. (No abnormalities with JIS K6267 stain test)

사양

- 재질: C-30-CS-1~4·7~10-EP-UL/에틸렌 프로필렌 고무(EPDM)
- C-30-CS-5·6/폴리에틸렌(PE)

용도

- 소형 분전반 도어의 쿠션용 계측기기의 고무 다리

비고


- 실록산 가스를 뺀 실리콘제도 제작합니다.
- 다른 컬러도 제작합니다. (CS-5·CS-6은 제외)
- 니트릴 고무제(NBR)로 적용 판 두께 1mm 용·1.2mm용도 제작합니다. (C-30-CS-7~10)

Specifications

- Material: C-30-CS-1~4·7~10-EP-UL: Ethylene propylene rubber (EPDM)
- C-30-CS-5·6: Polyethylene (PE)

Specific-use

- For small distribution board doors and measuring equipment.

참고 패널 구멍 치수
Reference panel drilling dimensions

C-30-CS-1-EP-UL



C-30-CS-2-EP-UL



C-30-CS-3-EP-UL



C-30-CS-4-EP-UL




C-30-CS-5




C-30-CS-6


[C-30-CS-1-EP-UL]




[C-30-CS-2-EP-UL]




[C-30-CS-3-EP-UL]




[C-30-CS-4-EP-UL]




[C-30-CS-7-EP-UL]




[C-30-CS-8-EP-UL]




[C-30-CS-5]




[C-30-CS-6]



[C-30-CS-9-EP-UL]



[C-30-CS-10-EP-UL]



상품번호 Product No.	RoHS 10	φd	경도 Hardness	제품질량(g) Mass	코드 Code
C-30-CS-1-EP-UL	●	φ17	50' ±5'		24103
C-30-CS-2-EP-UL	●	φ9.2	70' ±5'		24104
C-30-CS-3-EP-UL	●	φ8.2		0.9	24105
C-30-CS-4-EP-UL	●	φ5.4	50' ±5'	0.5	24106
C-30-CS-5	●	φ8.8	67D 스케일	0.9	20257
C-30-CS-6	●	φ8.8	67D scale	1.4	20258

●: RoHS10 대응품

▲: RoHS10에 대응 가능합니다.

상품번호 Product No.	RoHS 10	φd	경도 Hardness	제품질량(g) Mass	코드 Code
C-30-CS-7-EP-UL	●	φ4.8	50' ±5'	0.4	24107
C-30-CS-8-EP-UL	●	φ6.2		0.6	24108
C-30-CS-9-EP-UL	●	φ7.8			24109
C-30-CS-10-EP-UL	●	φ9.4			24110

●: RoHS10 대응품

▲: RoHS10에 대응 가능합니다.